



## Cable Gland Stainless Steel IP68 Metric

**1.4305 / AISI 303**

- Integrated anchorage
- Protection against twisting by the construction of the lamellar insert.
- Easy-to-install

### Specification

<b>MATERIAL</b>	Stainless Steel 1.4305
<b>LAMELLAR INSERT</b>	Polyamide PA6 V-2
<b>SEALING RING</b>	Polychloroprene-Nitrile rubber CR/NBR
<b>O-RING</b>	Nitrile Rubber NBR
<b>INGRESS PROTECTION</b>	IP68
<b>TEMPERATURE RANGE</b>	-20°C...+100°C (dynamisk) -40°C (static, short term)
<b>COLOUR</b>	Stainless Steel
<b>TEST STANDARD</b>	UL 514B
<b>UL / CSA-FILE</b>	E140310
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1475054	M12x1,5	3 - 6	5	25	14	15,5	50
1475055	M16x1,5	5 - 9	5	30	17	19	50
1475056	M20x1,5	9 - 13	6	33,5	22	24	50
1475057	M25x1,5	11 - 16	7	36,5	27	30	50
1475058	M32x1,5	14 - 20	8	38	34	36	25
1475059	M40x1,5	19 - 27	8	41	43	46	10
1475060	M50x1,5	24 - 35	9	49,5	55	60	5
1475061	M63x1,5	32 - 42	10	52,5	65	70	5