



## TKS - KLIKSEAL® RAL 9005

Material thickness 2 - 5 mm

- Integrated cable anchorage
- Handles large range of cable and pipe diameter
- Quick and simple assembly without the use of tools
- Ergonomic installation

### Specification

(1) Unstressed material.

#### INFORMATION\_KLIKSEAL

\* Cable Anchorage Type A, according to EN 50262.

\*\* 8,1 - 8,9 mm only approved for tension relief.

\*\*\* Varies depending on the thickness of material installed in.

<b>MATERIAL</b>	TPE and Polyamide 66 UL listed material
<b>INGRESS PROTECTION</b>	IP65
<b>TEMPERATURE RANGE</b>	-20°C....+125°C (1)
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	EN60529:1991 + A1, EN50262:1998 + A1 + A2
<b>SEMKO REPORT</b>	1906922
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	SIZE	IP65 AND CABLE ANCHORAGE TYPE A* FOR CABLE Ø MM	A MM	B MM	D*** MM	D1 MM	H MM	H2 MM	PCS/PACK
1475811	M20	7 - 11	20.5	2 - 5	29,3 - 34,5	4	17 - 20	5.5	50
1475812	M25	7 - 13**	25.5	2 - 5	34,3 - 40,0	5	17 - 20	5.5	50