



TSS MULTI RAL9010 V0 PG

Suitable for holes in material of 0,5 - 3,5 mm thickness.

- Quick and simple assembly without the use of tools
- Handles exceptionally large cable span
- An end-plug for all applications
- Material is UL94 V0 classified

Specification

(1) Unstressed material.

INFORMATION_KLIKSEAL

* Varies depending on the thickness of material installed in.

MATERIAL	TPE V0 - Thermoplastic Elastomer - UL listed material
INGRESS PROTECTION	IP67
TEMPERATURE RANGE	-40°C...+80°C (1)
COLOUR	White RAL 9010
TEST STANDARD	EN60670-1:2005+A1:2013
SEMKO REPORT	SE-S-2100893
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D* MM	D1 MM	H MM	H1 MM	H2* MM	PCS/PACK
TSS PG11 3x4-6 RAL9010 V0	PG11/18,6	3 x 4 - 6	19	0,5 - 3	26	3	11	4	6.75	50
TSS PG16 3x4-8 RAL9010 V0	PG16/22,5	3 x 4 - 8	23	0,5 - 3,5	30	3	11	4	6.75	50