



TSS RAL7035 V0 PG

Suitable for holes in material of 0,5 - 4,5 mm thickness.

- Quick and simple assembly without the use of tools
- Handles exceptionally large cable span
- An end-plug for all applications
- Material is UL94 V0 classified

Specification

(1) Unstressed material.

INFORMATION_KLIKSEAL

* Varies depending on the thickness of material installed in.

MATERIAL	TPE V0 - Thermoplastic Elastomer - UL listed material
INGRESS PROTECTION	IP67
TEMPERATURE RANGE	-40°C...+80°C (1)
COLOUR	Lightgrey RAL 7035
TEST STANDARD	EN60670-1:2005+A1:2013
SEMKO REPORT	SE-S-2100893
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D* MM	D1 MM	H MM	H1 MM	H2* MM	PCS/PACK
TSS PG9 RAL7035 V0	PG9/15,2	5 - 10	16	0,5 - 3	24	4	11	4	6.75	50
TSS PG11 RAL7035 V0	PG11/18,6	6 - 12	19	0,5 - 3	26	5	11	4	6.75	50
TSS PG16 RAL7035 V0	PG16/22,5	8 - 15	23	0,5 - 3,5	30	7	11	4	6.75	50
TSS PG21 RAL7035 V0	PG21/28,3	10 - 20	29	0,5 - 4,5	36	9	11	4	6.75	25
TSS PG29 RAL7035 V0	PG29/37,0	18 - 27	38	1,5 - 4,5	45	17	13.5	4.84	7.41	25