



## TSS RAL9005 V0 Metric

Suitable for holes in material of 0,5 - 4,5 mm thickness.

- Quick and simple assembly without the use of tools
- Handles exceptionally large cable span
- An end-plug for all applications
- Material is UL94 V0 classified

## Specification

(1) Unstressed material.

INFORMATION\_KLIKSEAL

\* Varies depending on the thickness of material installed in.

<b>MATERIAL</b>	TPE V0 - Thermoplastic Elastomer - UL listed material
<b>INGRESS PROTECTION</b>	IP67
<b>TEMPERATURE RANGE</b>	-40°C...+80°C (1)
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	EN60670-1:2005+A1:2013
<b>SEMKO REPORT</b>	SE-S-2100893
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D* MM	D1 MM	H MM	H1 MM	H2* MM	PCS/PACK
1475758	M16	5 - 10	16.5	0,5 - 3	23.5	4	11	4	6.75	50
1475759	M20	6 - 13	20.5	0,5 - 3	27.5	5	11	4	6.75	50
1475760	M25	8 - 17	25.5	0,5 - 3,5	32.5	7	11	4	6.75	50
1475761	M32	12 - 24	32.5	0,5 - 4,5	39.5	11	11	4	6.75	25
1475762	M40	19 - 31	40.5	1,5 - 4,5	47.5	18	13.5	4.84	7.41	25