



TSS RAL9010 Metric

Suitable for holes in material of 0,5 - 4,5 mm thickness.

- Quick and simple assembly without the use of tools
- Handles exceptionally large cable span
- An end-plug for all applications

Specification

(1) Unstressed material.

INFORMATION_KLIKSEAL

* Varies depending on the thickness of material installed in.

MATERIAL	TPE - Thermoplastic Elastomer - UL listed material
INGRESS PROTECTION	IP67
TEMPERATURE RANGE	-50°C...+125°C (1)
COLOUR	White RAL 9010
TEST STANDARD	EN60670-1:2005+A1:2013
SEMKO REPORT	SE-S-2100893
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D* MM	D1 MM	H MM	H1 MM	H2* MM	PCS/PACK
1475721	M16	5 - 10	16.5	0,5 - 3	23.5	4	11	4	6.75	50
1475722	M20	6 - 13	20.5	0,5 - 3	27.5	5	11	4	6.75	50
1475723	M25	8 - 17	25.5	0,5 - 3,5	32.5	7	11	4	6.75	50
1475724	M32	12 - 24	32.5	0,5 - 4,5	39.5	11	11	4	6.75	25
1475725	M40	19 - 31	40.5	1,5 - 4,5	47.5	18	13.5	4.84	7.41	25