



Sensor PMXX

Halogen free drag-chain sensor cable

Specification

RATED VOLTAGE UO/U CONTROL CORES	300V
CONDUCTOR CLASS	Class 6 = extra fine stranded wires
CONDUCTOR MATERIAL	Copper
CORE INSULATION	Polyolefin
CORE IDENTIFICATION	3 cores Brown+Blue+Black 4 cores Brown+White+Blue+Black 5 cores Brown+White+Blue+Black+Green/yel
PROTECTIVE CONDUCTOR	-
OUTER SHEATH	PUR
SHEATH COLOUR	Black
BENDING RADIUS FIXED	3 x cable diameter
BENDING RADIUS MOVED	6 x cable diameter
MIN OPERATING TEMPERATURE FIXED	-50°C
MAX OPERATING TEMPERATURE FIXED	+80°C
MIN OPERATING TEMPERATURE MOVED	-40°C
MAX OPERATING TEMPERATURE MOVED	+80°C
TESTING VOLTAGE	2000V
FLAME RETARDANT	IEC 60332-1

Variants

E-NUMBER	DIMENSION N X MM ²	OUTER DIAMETER MM	WEIGHT KG/100M
N8337190	3x0,34	4.5	3.5
N8337200	4x0,34	4.9	3.8
5G0,5	6.3	4.1	