



SKX (H03VVH2-F)

PVC-sheathed installation cable

Specification

| | |
|---------------------------------|-------------------------------|
| STANDARD | HD 21.5 |
| APPROVALS | Cenelec HAR |
| RATED VOLTAGE U ₀ /U | 300/300V |
| CONDUCTOR CLASS | Class 5 = fine stranded wires |
| CONDUCTOR MATERIAL | Copper |
| CORE INSULATION | PVC |
| CORE IDENTIFICATION | Blue and Brown |
| OUTER SHEATH | PVC |
| BENDING RADIUS FIXED | 6 x cable diameter |
| BENDING RADIUS MOVED | 6 x cable diameter |
| MIN OPERATING TEMPERATURE FIXED | -40°C |
| MAX OPERATING TEMPERATURE FIXED | +70°C |
| MIN OPERATING TEMPERATURE MOVED | +5°C |
| MAX OPERATING TEMPERATURE MOVED | +70°C |
| TESTING VOLTAGE | 2000V |
| FLAME RETARDANT | IEC 60332-1 |

Variants

| E-NUMBER | DIMENSION N X MM ² | OUTER DIMENSIONS H X B MM | WEIGHT KG/100M | COLOUR | LENGTH | PACKAGING TYPE |
|----------|-------------------------------|---------------------------|----------------|--------|------------|----------------|
| 0508202 | 2x0,75 | 3,5 x 6,0 | 2.6 | White | 100 meters | Ring |
| N9270413 | 2x0,75 | 3,5 x 6,0 | 2.6 | Black | 100 meters | Bobin |