



## Novoflex HEAVY LIFT-H

PVC-sheathed lift cable

### Specification

STANDARD	VDE 0295
RATED VOLTAGE U <sub>0</sub> /U	300/500V
CONDUCTOR CLASS	Class 5 = fine stranded wires
CONDUCTOR MATERIAL	Copper
CORE INSULATION	PVC
CORE IDENTIFICATION	Black with white numerals
PROTECTIVE CONDUCTOR	Yellow/Green
OUTER SHEATH	Special PVC
SHEATH COLOUR	Black
BENDING RADIUS FIXED	20 x cable diameter
BENDING RADIUS MOVED	20 x cable diameter
MIN OPERATING TEMPERATURE FIXED	-15°C
MAX OPERATING TEMPERATURE FIXED	+70°C
MIN OPERATING TEMPERATURE MOVED	-15°C
MAX OPERATING TEMPERATURE MOVED	+70°C
TESTING VOLTAGE	3000V
FLAME RETARDANT	IEC 60332-1

## Variants

E-NUMBER	DIMENSION N X MM <sup>2</sup>	OUTER DIAMETER MM	WEIGHT KG/100M
N8613070	7G1,0	14.9	23.2
N8613120	12G1,0	20	41.5
N8613180	18G1,0	21.4	46.2
N8613240	24G1,0	23.2	61.5
N8613360	36G1,0	29	96.6