



Spiral cable H05BQ-F

Rubber insulated PUR-sheathed spiral cable

Specification

APPROVALS	Cenelec HAR
RATED VOLTAGE UO/U	300/500V
CONDUCTOR CLASS	Class 6 = extra fine stranded wires
CONDUCTOR MATERIAL	Copper
CORE INSULATION	Rubber (7 cores = TPE)
CORE IDENTIFICATION	≤5 cores: Colour coded, ≥7 cores: Black with numerals
PROTECTIVE CONDUCTOR	Yellow/Green
OUTER SHEATH	PUR
MIN OPERATING TEMPERATURE MOVED	-30°C
MAX OPERATING TEMPERATURE MOVED	+60°C
TESTING VOLTAGE	2000-3000V
FLAME RETARDANT	IEC 60332-1

Variants

E-NUMBER	DIMENSION N X MM ²	RETRACTED SPIRAL LENGTH MM	EXTENDED SPIRAL LENGTH MM	LENGTH OF END MM	OUTER DIAM COILED CABLE MM	COLOUR
2404124	2x0,75	500	2000	500	23.6	Black
2404125	2x0,75	1000	4000	500	23.6	Black
2404126	2x0,75	1500	6000	500	23.6	Black
N8205103	2x0,75	1500	6000	2500	23.6	Black
2404127	3G0,75	500	2000	500	26	Black
2404128	3G0,75	1000	4000	500	26	Black
2404129	3G0,75	1500	6000	500	26	Black
N8205113	3G0,75	1500	6000	2500	26	Black
2404130	4G0,75	500	2000	500	29.2	Black
2404131	4G0,75	1000	4000	500	29.2	Black
2404132	4G0,75	1500	6000	500	29.2	Black
N8205123	4G0,75	1500	6000	2500	29.2	Black
2404133	5G0,75	500	2000	500	30.8	Black
2404134	5G0,75	1000	4000	500	30.8	Black
2404135	5G0,75	1500	6000	500	30.8	Black
N8205133	5G0,75	1500	6000	2500	30.8	Black
2404136	7G0,75	500	2000	500	40.6	Grey
2404137	7G0,75	1000	4000	500	40.6	Grey
2404138	7G0,75	1500	6000	500	40.6	Grey
N8205143	7G0,75	1500	6000	2500	40.6	Grey