


**QUICK-CONNECT**  
VON BALS

## Appliance Inlet with Flange Quick-Connect

### Specification

|                            |  |
|----------------------------|--|
| <b>MATERIAL ENCLOSURE</b>  | Polyamide PA6  |
| <b>MATERIAL TERMINALS</b>  | Brass  |
| <b>CONNECTION CAPACITY</b> | 16A max. 2,5mm <sup>2</sup><br>32A max. 6mm <sup>2</sup> |
| <b>INGRESS PROTECTION</b>  | IP44   |
| <b>HALOGEN-FREE</b>        | Yes  |

## Variants

| E-NUMBER | ARTICLE NO. | DESCRIPTION | NUMBER OF POLES | VOLTAGE / COLOR CODE | RATED CURRENT A | FIXING HOLES MM | PCS/PACK |
|----------|-------------|-------------|-----------------|----------------------|-----------------|-----------------|----------|
| 2421755  | 28111       | 216-6       | 3               | 230V / Blue          | 16              | 60 x 60         | 10       |
| -        | 28017       | 316-9       | 4               | 230V / Blue          | 16              | 60 x 60         | 10       |
| -        | 28006       | 416-9       | 5               | 230V / Blue          | 16              | 60 x 60         | 10       |
| 2421758  | 28010       | 232-6       | 3               | 230V / Blue          | 32              | 60 x 60         | 10       |
| -        | 28011       | 332-9       | 4               | 230V / Blue          | 32              | 60 x 60         | 10       |
| -        | 28015       | 432-9       | 5               | 230V / Blue          | 32              | 60 x 60         | 10       |
| 2421756  | 28112       | 316-6       | 4               | 400V / Red           | 16              | 60 x 60         | 10       |
| 2421757  | 282001      | 416-6       | 5               | 400V / Red           | 16              | 60 x 60         | 10       |
| 2421759  | 28012       | 332-6       | 4               | 400V / Red           | 32              | 60 x 60         | 10       |
| 2421760  | 282002      | 432-6       | 5               | 400V / Red           | 32              | 60 x 60         | 10       |