


**QUICK CONNECT**  
VON BALS

## Surface Mounting Appliance Inlet Quick-Connect

### Specification

MATERIAL ENCLOSURE	Polyamide PA6
MATERIAL TERMINALS	Brass
CONNECTION CAPACITY	16A max. 2,5mm <sup>2</sup> 32A max. 6mm <sup>2</sup>
INGRESS PROTECTION	IP44
HALOGEN-FREE	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	NUMBER OF POLES	VOLTAGE / COLOR CODE	RATED CURRENT A	CABLE ENTRIES MM	PCS/PACK
2421730	24423	216-6	3	230V / Blue	16	M20	10
-	24393	316-9	4	230V / Blue	16	M25	10
-	24400	416-9	5	230V / Blue	16	M25	10
2421733	24402	232-6	3	230V / Blue	32	M25	10
-	24404	332-9	4	230V / Blue	32	M25	10
-	24407	432-9	5	230V / Blue	32	M25	10
2421731	24392	316-6	4	400V / Red	16	M25	10
2421732	242001	416-6	5	400V / Red	16	M25	10
2421734	24405	332-6	4	400V / Red	32	M25	10
2421735	242002	432-6	5	400V / Red	32	M25	10