



Connector Innolinq IP67

INNOLINQ-design

- Connector INNOLINQ with screw terminals and Multi-Grip
- IP67
- Screwless enclosure connection
- Simultaneous cable gland and seal

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	63A: 6 - 16mm ² 125A: 16 - 50mm ²
INGRESS PROTECTION	IP67

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	RATED CURRENT A	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
-	3181	263-6	63	3	230V / Blue	16 - 36	5
-	3185	363-6	63	4	400V / Red	16 - 36	5
2421782	3124	463-6	63	5	400V / Red	16 - 36	5
-	3191	2125-6	125	3	230V / Blue	26 - 50	5
-	3194	3125-9	125	4	230V / Blue	26 - 50	5
-	3198	4125-9	125	5	230V / Blue	26 - 50	5
-	3192	2125-9	125	3	400V / Red	26 - 50	5
2421784	3195	3125-6	125	4	400V / Red	26 - 50	5
2421786	3199	4125-6	125	5	400V / Red	26 - 50	5