



Plug Innolinq IP67

INNOLINQ-design

- Plug INNOLINQ with screw terminals and Multi-Grip
- IP67
- Screwless enclosure connection
- Simultaneous cable gland and seal

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	63A: 6 - 16mm ² 125A: 16 - 50mm ²
INGRESS PROTECTION	IP67

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	RATED CURRENT A	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
-	2181	263-6	63	3	230V / Blue	16 - 36	5
-	2185	363-6	63	4	400V / Red	16 - 36	5
2421781	2189	463-6	63	5	400V / Red	16 - 36	5
-	2191	2125-6	125	3	230V / Blue	26 - 50	5
-	2194	3125-9	125	4	230V / Blue	26 - 50	5
-	2198	125	5	230V / Blue	26 - 50	5	
-	2192	2125-9	125	3	400V / Red	26 - 50	5
2421783	2195	3125-6	125	4	400V / Red	26 - 50	5
2421785	2199	4125-6	125	5	400V / Red	26 - 50	5
-	2196	3125-7	125	4	500V / Black	26 - 50	5
-	21555	4125-7	125	5	500V / Black	26 - 50	5