

QUICK-CONNECT<sup>®</sup>  
VON BALS

## Straight Panel Mounting Socket Outlet Quick-Connect

**16A / 32A**

- Flange 75x75mm

### Specification

MATERIAL ENCLOSURE	Polyamide PA6
MATERIAL TERMINALS	Brass
CONNECTION CAPACITY	16A max. 4mm <sup>2</sup> 32A max. 10mm <sup>2</sup>
INGRESS PROTECTION	IP44
HALOGEN-FREE	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	FIXING HOLES MM	PCS/PACK
-	13692	316-9	16	4	230V / Blue	60 x 60	10
-	13698	416-9	16	5	230V / Blue	60 x 60	10
-	13687	216-9	16	3	400V / Red	60 x 60	10
2421741	13693	316-6	16	4	400V / Red	60 x 60	10
2421743	13703	232-6	32	3	230V / Blue	60 x 60	10
-	13709	332-9	32	4	230V / Blue	60 x 60	10
-	13715	432-9	32	5	230V / Blue	60 x 60	10
-	13704	232-9	32	3	400V / Red	60 x 60	10
2421744	13710	332-6	32	4	400V / Red	60 x 60	10