

QUICK CONNECT<sup>®</sup>  
VON BALS

## Surface Mounting Socket Outlet Quick-Connect

16A / 32A

### Specification

MATERIAL ENCLOSURE	Polyamide PA6
MATERIAL TERMINALS	Brass
CONNECTION CAPACITY	16A max. 4mm <sup>2</sup> 32A max. 10mm <sup>2</sup>
INGRESS PROTECTION	IP44
HALOGEN-FREE	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
2421720	11895	216-6	16	3	230V / Blue	M20	10
-	11910	316-9	16	4	230V / Blue	M25	10
2421721	11905	316-6	16	4	400V / Red	M25	10
2421722	112001	416-6	16	5	400V / Red	M25	10
2418347	11914	16	4	500V / Black	M25	10	
2421723	11919	232-6	32	3	230V / Blue	M25	10
-	11921	332-9	32	4	230V / Blue	M25	10
2421724	11922	332-6	32	4	400V / Red	M25	10
2421725	112002	432-6	32	5	400V / Red	M25	10
2418348	11924	332-7	32	4	500V / Black	M25	10