



Straight, IP69, metric thread

Very high impact resistance
FDA 21 CFR / EU 10/2011 compliant polyamide 6 material
Ecolab certificate
NSF14159-1; NSF169 (application areas - splash zone)
UL Recognition according to UL1696 (file E80294)
Excellent conduit pull-out strength
Fits both conduit profiles - fine (T) and coarse (G)
RoHS and REACH compliant
Free from halogens and cadmium

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	D1 MM	D2 MM	SW MM	PCS/PACK
JKNH-M162	M16x1,5	12	47.5	11	28.5	25	10
JKNH-M202	M20x1,5	12	47.5	12.5	28.5	25	10
JKNH-M207	M20x1,5	17	53.5	14.5	35	32	10
JKNH-M257	M25x1,5	17	54.5	16.5	35	32	10
JKNH-M253	M25x1,5	23	57	19	42	38	10
JKNH-M323	M32x1,5	23	60.5	23	43	38	10
JKNH-M329	M32x1,5	29	63.5	26	51.5	46	10
JKNH-M409	M40x1,5	29	69.5	29	51.5	46	10
JKNH-M406	M40x1,5	36	75	32	65	60	10
JKNH-M506	M50x1,5	36	75	37.5	65	60	10
JKNH-M508	M50x1,5	48	81	42	75	70	10
JKNH-M638	M63x1,5	48	81	48.5	75	70	10