



## Screening braid

- High-quality shielding.
- Supplied on tube to maintain shape.

### Specification

MATERIAL	Tinned Copper
TEMPERATURE RANGE	-75°C...+450°C
COVERAGE	> 90%
COLOUR	Tinned Copper

## Variants

E-NUMBER	ARTICLE NO.	SIZE	BRAID SPEC.	RANGE OF APPLICATION Ø MM	PCS/PACK
1411300	F.CK.03	3,0	Ø 0,13mm	2,0 - 3,5	100
1411302	F.CK.04	4,0	Ø 0,13mm	3,0 - 5,0	100
1411304	F.CK.06	6,0	Ø 0,13mm	5,0 - 7,0	100
1411306	F.CK.10	10,0	Ø 0,16mm	7,0 - 12,0	100
1411308	F.CK.12,5	12,5	Ø 0,16mm	11,0 - 13,0	100
1411310	F.CK.15	15,0	Ø 0,20mm	13,0 - 18,0	100
1411312	F.CK.20	20,0	Ø 0,13mm	17,0 - 23,0	50
1411314	F.CK.25	25,0	Ø 0,13mm	22,0 - 28,0	50
1411316	F.CK.30	30,0	Ø 0,16mm	27,0 - 36,0	50
1411318	F.CK.35	35,0	Ø 0,16mm	30,0 - 50,0	50