



Curved elbow conduit-connector 90° with metal thread IP68 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	Ø D MM	A MM	B MM	Ø C MM	R MM	Ø ID MM	PCS/PACK
NVBV-P167	PG 16	17	13	29	54	73	29.5	30.5	14.5	50
NVBV-P213	PG 21	23	14	35	65.5	85	37	38	19.5	30
NVBV-P299	PG 29	29	14	46	75	96	44	45	28.5	20
NVBV-P366	PG 36	36	17	55	90.5	123	53.5	53	36	20
NVBV-P488	PG 48	48	17	69	103.5	135	66	60	48	10