



Elbow conduit-connector 45° with metal thread IP68 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	A MM	B MM	C MM	Ø ID MM	Ø D MAX MM	PCS/PACK
NVAV-M120-10	M12x1,5	10	10	48.5	37	27	5.7	20	50
NVAV-M120-5	M12x1,5	10	5	43.5	37	27	5.7	20	50
NVAV-M162-10	M16x1,5	12	10	50.5	41.5	29.5	9.5	24	50
NVAV-M162-5	M16x1,5	12	5	48	40.5	28.5	9.7	24	50
NVAV-M207-10	M20x1,5	17	10	60.5	52.5	38	13.5	29.5	50
NVAV-M207-6	M20x1,5	17	6	56.5	51.5	37	13.7	30	50
NVAV-M253-11	M25x1,5	23	11	69	61	43.5	18.5	37	30
NVAV-M253-7	M25x1,5	23	7	66	60.5	43	18.6	37	30
NVAV-M257-11	M25x1,5	17	11	61.5	55.5	38	17	35	50
NVAV-M323-13	M32x1,5	23	13	71	65	43.5	23	43	30
NVAV-M329-13	M32x1,5	29	13	76.5	68.5	47	25.5	44	20
NVAV-M329-8	M32x1,5	29	8	72	68	46.5	25.7	44	20
NVAV-M406-13	M40x1,5	36	13	94	87.5	60	33	55	20
NVAV-M406-8	M40x1,5	36	8	89	87.5	60	33	55	20
NVAV-M409-13	M40x1,5	29	13	78	73.5	47	30.5	53	20
NVAV-M506-14	M50x1,5	36	14	95	92.5	60	38.5	65	20
NVAV-M508-14	M50x1,5	48	14	102	101	66.5	42.3	69	10
NVAV-M508-9	M50x1,5	48	9	97	101	66.5	42.3	69	10
NVAV-M638-14	M63x1,5	48	14	102	104	66.5	52	75	10
NVAV-M638-10	M63x1,5	48	10	98	104	66.5	52	75	10