



Elbow conduit-connector 45° with metal thread IP68 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	A MM	B MM	C MM	Ø ID MM	Ø D MAX MM	PCS/PACK
NVAV-P090	PG9	10	12	50.5	37	27	9.6	20	50
NVAV-P112	PG11	12	12	55	40.5	28.5	12.5	24	50
NVAV-P137	PG13,5	17	13	63.5	50	36	14.6	30	50
NVAV-P167	PG16	17	13	63.5	50	36	16.5	30	50
NVAV-P213	PG21	23	14	73	60.5	43	22.4	37	30
NVAV-P299	PG29	29	14	78	68	46.5	30.5	44	20
NVAV-P366	PG36	36	17	98	87.5	60	38.5	53	20
NVAV-P488	PG48	48	17	105	101	66.5	51	65	10