



Elbow conduit-connector 90° with metal thread IP68 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	A MM	B MM	Ø ID MM	Ø D MAX MM	PCS/PACK
NVWV-P090	PG 9	10	12	39.5	39.5	9	20	50
NVWV-P112	PG 11	12	12	45.5	45	12	24	50
NVWV-P137	PG 13,5	17	13	50	58.5	14	29.5	50
NVWV-P167	PG 16	17	13	50	58.5	16	29.5	50
NVWV-P213	PG 21	23	14	62	67	21.5	37	30
NVWV-P299	PG 29	29	14	69	74.5	29.5	44	20
NVWV-P366	PG 36	36	17	83.5	98.5	38	56	20
NVWV-P488	PG 48	48	17	97	111.5	49.5	70	10