



## Rak slangförskruvning med metallgänga IP69 metrisk

- For applications with high technical requirements and in most demanding climatic conditions.
- Specially formulated polyamide 6
- Nickel-plated brass thread.
- Screwdriver required for dismantling, impeding unauthorised or accidental opening.
- Easy push-in assembly for maximum installation reliability.
- High thread and system connection strengths.
- Very high impact resistance.
- High conduit pull-out strength.
- Fits both conduit profiles - fine (T) and coarse (G).

### Specification

<b>MATERIAL</b>	Polyamide PA6
<b>TEMPERATURE RANGE</b>	-50°C...+105°C
<b>COLOUR</b>	Black RAL 9005
<b>HALOGEN-FREE</b>	Yes

## Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	H MM	SW MM	E MM	E1 MM	PCS/PACK
NKNH-M120-10	M12x1,5	10	10	45.00	22	5.50	25	50
NKNH-M160-10	M16x1,5	10	10	45.00	22	9.50	25	50
NKNH-M162-10	M16x1,5	12	10	50.50	25	9.50	28.5	50
NKNH-M202-10	M20x1,5	12	10	50.50	25	12.50	28.5	50
NKNH-M207-10	M20x1,5	17	10	56.00	32	13.50	35	50
NKNH-M257-11	M25x1,5	17	11	57.00	32	16.50	35	50
NKNH-M253-11	M25x1,5	23	11	59.50	38	18.50	42	30
NKNH-M323-13	M32x1,5	23	13	61.50	38	23.00	43	30
NKNH-M329-13	M32x1,5	29	13	67.00	46	25.50	51.5	20
NKNH-M409-13	M40x1,5	29	13	68.50	46	29.00	53	20
NKNH-M406-13	M40x1,5	36	13	74.00	60	32.50	65	20
NKNH-M506-14	M50x1,5	36	14	75.00	60	37.00	65	20
NKNH-M508-14	M50x1,5	48	14	81.00	70	42.00	75	10
NKNH-M638-14	M63x1,5	48	14	81.00	70	48.50	75	10