



## Straight conduit-connector with metal thread IP68 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

### Specification

<b>MATERIAL</b>	Polyamide 6 (PA6)
<b>INGRESS PROTECTION</b>	IP68
<b>TEMPERATURE RANGE</b>	-40°C...+105°C
<b>COLOUR</b>	Black RAL 9005
<b>HALOGEN-FREE</b>	Yes

## Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	L MM	SW MM	Ø ID MM	Ø D MAX MM	PCS/PACK
NVNV-M120-10	M12x1,5	10	10	40	19	5.5	21	50
NVNV-M120-5	M12x1,5	10	5	35	19	5.5	21	50
NVNV-M160-10	M16x1,5	10	10	40	19	9.5	24	50
NVNV-M160-5	M16x1,5	10	5	35	19	9.5	24	50
NVNV-M162-10	M16x1,5	12	10	43	24	9.5	26	50
NVNV-M162-5	M16x1,5	12	5	38	24	9.5	26	50
NVNV-M202-10	M20x1,5	12	10	43	24	13.5	28	50
NVNV-M202-6	M20x1,5	12	6	39	24	13.5	28	50
NVNV-M207-10	M20x1,5	17	10	51	30	13.5	33	50
NVNV-M207-6	M20x1,5	17	6	47	30	13.5	33	50
NVNV-M257-11	M25x1,5	17	11	52	30	18	35	50
NVNV-M257-7	M25x1,5	17	7	48	30	18	35	50
NVNV-M253-11	M25x1,5	23	11	54	36	18.5	39	30
NVNV-M253-7	M25x1,5	23	7	50	36	18.5	39	30
NVNV-M323-13	M32x1,5	23	13	56	36	24	43	30
NVNV-M323-8	M32x1,5	23	8	51	36	24	43	30
NVNV-M329-13	M32x1,5	29	13	57.3	46	25	50	20
NVNV-M329-8	M32x1,5	29	8	52.3	46	25	50	20
NVNV-M409-13	M40x1,5	29	13	57.3	46	31.5	53	20
NVNV-M409-8	M40x1,5	29	8	52.3	46	31.5	53	20
NVNV-M406-13	M40x1,5	36	13	71.4	55	32.5	59	20
NVNV-M406-8	M40x1,5	36	8	66.4	55	32.5	59	20
NVNV-M506-14	M50x1,5	36	14	72.4	55	39.5	65	20
NVNV-M506-9	M50x1,5	36	9	67.4	55	39.5	65	20
NVNV-M508-14	M50x1,5	48	14	72.4	55	41.5	71	10
NVNV-M508-9	M50x1,5	48	9	67.4	65	41.5	71	10
NVNV-M638-14	M63x1,5	48	14	72.4	65	41.5	75	10
NVNV-M638-10	M63x1,5	48	10	68.4	65	41.5	75	10