



Straight conduit-connector with metal thread IP68 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONNECTION THREAD	INTERNAL Ø MM	CONDUIT SIZE	G MM	L MM	SW MM	Ø ID MM	Ø D MAX MM	PCS/PACK
NVNV-P090	PG 9	9.6	10	12	42	19	9.6	21	50
NVNV-P112	PG 11	12.5	12	12	45	24	12.5	26	50
NVNV-P137	PG 13,5	14.5	17	13	54	30	14.5	33	50
NVNV-P167	PG 16	16.5	17	13	54	30	16.5	33	50
NVNV-P213	PG 21	22	23	14	57	36	22	39	30
NVNV-P293	PG 29	26.5	23	14	62.5	36	26.5	43	30
NVNV-P299	PG 29	30	29	14	58.5	46	30	50	20
NVNV-P366	PG 36	40	36	17	75.5	55	40	59	20
NVNV-P488	PG 48	50	48	17	75.5	66	50	71	10