



## Sviveladapter

- For connection with connectors with metal thread.
- Nickel-plated brass)
- Connectors to swivel freely in applications where such movement is occasionally necessary.  
With thread edge protection

## Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>INGRESS PROTECTION</b>	IP68
<b>TEMPERATURE RANGE</b>	-40°C....+105°C

## Variants

ARTICLE NO.	CONNECTION THREAD	INTERNAL THREAD	G MM	L MM	Ø D MM	Ø D1 MM	A MM	B MM	C MM	SW MM	PCS/PACK
SWA-M16-10	M16x1,5	M16x1,5	10	10	23	7.0	37.5	26,5	11,0	21	1
SWA-M20-10	M20x1,5	M20x1,5	10	10	27	10.0	38.5	27,5	11,0	25	1
SWA-M25-11	M25x1,5	M25x1,5	11	11	32	15.5	41	29,0	12,0	30	1
SWA-M32-13	M32x1,5	M32x1,5	13	13	45	22.0	46.5	32,5	14,0	41	1
SWA-M40-13	M40x1,5	M40x1,5	13	13	55	29.0	47.5	33,5	14,0	50	1
SWA-M50-14	M50x1,5	M50x1,5	14	14	59	35.5	49.5	34,5	16,0	55	1
SWA-M63-14	M63x1,5	M63x1,5	14	14	75	45.5	52	37,0	15,0	70	1