



Curved elbow conduit-connector 90° IP66 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	B MM	H MM	E MM	E1 MM	R MM	PCS/PACK
1470132	BVBD-M207GT	M20x1,5	NW 17	11	73,0	47,5	15	11	30,5	50
1470133	BVBD-M257GT	M25x1,5	NW 17	12	76,0	48,5	18	14,5	30,5	50
1470134	BVBD-M253GT	M25x1,5	NW 23	12	83,0	57,5	21	15,5	38,0	30
1470135	BVBD-M323GT	M32x1,5	NW 23	15	87,5	61,0	24	19,5	38,0	30
1470136	BVBD-M329GT	M32x1,5	NW 29	15	93,0	70,5	28	23	45,0	20
1470137	BVBD-M409GT	M40x1,5	NW 29	19	98,5	74,5	34	28,5	45,0	20
1470138	BVBD-M406GT	M40x1,5	NW 36	19	121,0	85,0	36	29	53,0	20
1470139	BVBD-M506GT	M50x1,5	NW 36	19	125,0	85,0	41	36,5	53,0	20
1470140	BVBD-M508GT	M50x1,5	NW 48	19	130,0	98,5	46	38,5	60,0	10
1470141	BVBD-M638GT	M63x1,5	NW 48	19	138,0	98,5	55	48	60,0	10