



Curved elbow conduit-connector 90° IP66 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	B MM	H MM	E MM	E1 MM	R MM	PCS/PACK
1410692	BVBD-P167GT	PG16/22,5	NW 17	11	73,0	47,5	18	14,5	30,5	50
1410693	BVBD-P213GT	PG21/28,3	NW 23	12	85,0	57,5	24	19,5	38,0	30
1410694	BVBD-P299GT	PG29/37,0	NW 29	12	96,0	67,5	34	28,5	45,0	20
1410695	BVBD-P366GT	PG36/47,0	NW 36	13	123,0	79,0	41	36	53,0	20
1410696	BVBD-P488GT	PG48/59,3	NW 48	13	135,0	92,5	55	48	60,0	10