



Elbow conduit-connector 45° IP66 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	B MM	C MM	H MM	E1 MM	PCS/PACK
1470129	BVAD-M120GT	M12x1,5	NW 10	11	37,0	27,0	43,5	20	50
1470120	BVAD-M160GT	M16x1,5	NW 10	11	38,0	27,0	43,5	20	50
1470121	BVAD-M162GT	M16x1,5	NW 12	11	40,0	28,5	48,0	24	50
1470130	BVAD-M202GT	M20x1,5	NW 12	11	41,5	28,5	48,0	24	50
1470122	BVAD-M207GT	M20x1,5	NW 17	11	51,5	37,0	55,5	30	50
1470123	BVAD-M253GT	M25x1,5	NW 23	12	58,5	43,0	65,0	37	30
1470124	BVAD-M329GT	M32x1,5	NW 29	15	66,5	46,5	73,5	44	20
1470125	BVAD-M406GT	M40x1,5	NW 36	19	85,5	60,0	92,5	53	20
-	BVAD-M506GT	M50x1,5	NW 36	19	90,5	59	93,5	59	20
1470126	BVAD-M508GT	M50x1,5	NW 48	19	96,0	66,5	100,0	65	10
1410667	BVAD-M638GT	M63x1,5	NW 48	19	104,0	66,5	100,0	65	10