



Elbow conduit-connector 45° IP66 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	B MM	C MM	H MM	E1 MM	PCS/PACK
1410660	BVAD-P090GT	PG9/15,2	NW 10	11	37,0	27,0	43,5	20	50
1410661	BVAD-P112GT	PG11/18,6	NW 12	11	40,0	28,5	48,0	24	50
-	BVAD-P132GT	PG13,5/20,4	NW 12	11	41,5	28,5	48,0	24	50
1410662	BVAD-P167GT	PG16/22,5	NW 17	11	51,5	37,0	55,5	30	50
1410663	BVAD-P213GT	PG21/28,3	NW 23	11	58,0	42,0	63,0	37	30
1410664	BVAD-P299GT	PG29/37,0	NW 29	12	66,0	45,5	69,0	44	20
1410665	BVAD-P366GT	PG36/47,0	NW 36	13	86,0	60,0	86,0	53	20
1410666	BVAD-P488GT	PG48/59,3	NW 48	13	100,0	66,5	94,0	65	10