



Elbow conduit-connector 90° IP66 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	B MM	H MM	E1 MM	PCS/PACK
1410650	BVWD-P07MGT-11	PG7/12,5	NW 7	11	35,0	32,0	16,5	100
1410651	BVWD-P070GT-11	PG7/12,5	NW 10	11	39,5	34,0	20	50
-	BVWD-P09MGT-11	PG9/15,2	NW 7	11	36,5	32,0	16,5	100
1410652	BVWD-P090GT-11	PG9/15,2	NW 10	11	39,5	34,0	20	50
-	BVWD-P092GT-11	PG9/15,2	NW 12	11	44,5	38,5	23,5	50
-	BVWD-P110GT-11	PG11/18,6	NW 10	11	41,0	34,0	20	50
-	BVWD-P112GT-8	PG11/18,6	NW 12	8	46,0	35,5	23,5	50
1410653	BVWD-P112GT-11	PG11/18,6	NW 12	11	46,0	38,5	23,5	50
-	BVWD-P130GT-11	PG13,5/20,4	NW 10	11	42,5	34,0	20	50
-	BVWD-P132GT-11	PG13,5/20,4	NW 12	11	47,5	38,5	23,5	50
-	BVWD-P137GT-11	PG13,5/20,4	NW 17	11	58,5	43,5	29,5	50
1410654	BVWD-P167GT-11	PG16/22,5	NW 17	11	58,5	43,5	29,5	50
1410655	BVWD-P213GT	PG21/28,3	NW 23	11	67,0	54,0	37	30
1410656	BVWD-P299GT	PG29/37,0	NW 29	12	74,5	61,5	44	20
1410657	BVWD-P366GT	PG36/47,0	NW 36	13	98,0	72,0	53,5	20
1410658	BVWD-P488GT	PG48/59,3	NW 48	13	111,0	85,5	66	10