



Female Thread Adapter UNEF

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

| | |
|---------------------------|----------------------------------|
| MATERIAL | Polyamide PA6 |
| INGRESS PROTECTION | IP66 stat. / IP54 dyn. |
| TEMPERATURE RANGE | -40°C...+105°C |
| COLOUR | Black RAL 9005 |
| TEST STANDARD | EN 60529 / DIN 40050 / IEC 60529 |
| FLAME CLASS | UL94 V0 |
| GLOW WIRE TEST | 960°C acc. to EN 60695-2-10 |
| HALOGEN-FREE | Yes |

Variants

| ARTICLE NO. | INTERNAL THREAD | CONDUIT SIZE | L MM | H MM | E1 MM | PCS/PACK |
|-----------------|-----------------|--------------|------|------|-------|----------|
| BVIDA-U15MGT | 5/8"-24 | 7 | 8 | 31.5 | 21.5 | 100 |
| BVIDA-U150GT | 5/8"-24 | 10 | 8 | 33.5 | 21.5 | 50 |
| BVIDA-U152GT | 5/8"-24 | 12 | 8 | 36.5 | 21.5 | 50 |
| BVIDA-U180GT | 3/4"-20 | 10 | 8 | 33.5 | 27 | 50 |
| BVIDA-U182GT | 3/4"-20 | 12 | 8 | 36.5 | 27 | 50 |
| BVIDA-U187GT | 3/4"-20 | 17 | 8 | 44.5 | 27 | 50 |
| BVIDA-U232GT | 15/16"-20 | 12 | 8 | 38.5 | 32 | 50 |
| BVIDA-U237GT | 15/16"-20 | 17 | 8 | 46.5 | 32 | 50 |
| BVIDA-U233GT | 15/16"-20 | 23 | 8 | 48.5 | 35.5 | 30 |
| BVIDA-U323GT-11 | 1 5/16"-18 | 23 | 11 | 52.0 | 44 | 30 |
| BVIDA-U347GT | 1 3/8"-18 | 17 | 8 | 46.5 | 44 | 50 |
| BVIDA-U343GT | 1 3/8"-18 | 23 | 8 | 48.5 | 44 | 30 |
| BVIDA-U402GT | 1 5/8"-18 | 12 | 7 | 55.5 | 48 | 50 |
| BVIDA-U407GT | 1 5/8"-18 | 17 | 7 | 61.5 | 48 | 50 |
| BVIDA-U403GT | 1 5/8"-18 | 23 | 7 | 60.5 | 48 | 30 |