



Straight conduit-connector IP66 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1470098	BVND-M12MGT	M12x1,5	NW 7	11	34,5	14	20	100
1470099	BVND-M120GT	M12x1,5	NW 10	11	36,5	17	20	100
1470100	BVND-M160GT	M16x1,5	NW 10	11	36,5	17	23	100
1470101	BVND-M162GT	M16x1,5	NW 12	11	39,5	20	23,5	100
-	BVND-M200GT	M20x1,5	NW 10	11	36,5	17	26	100
1470102	BVND-M202GT	M20x1,5	NW 12	11	39,5	20	26	100
1470103	BVND-M207GT	M20x1,5	NW 17	11	47,5	26	29,5	100
-	BVND-M203GT	M20x1,5	NW 23	11	51,0	32	37	50
1470108	BVND-M257	M25x1,5	NW 17	12	48,5	26	32	100
1470104	BVND-M253GT	M25x1,5	NW 23	12	52,0	32	37	50
1470109	BVND-M323GT	M32x1,5	NW 23	15	55,5	32	43	50
1470105	BVND-M329GT	M32x1,5	NW 29	15	56,0	40	44	30
1470117	BVND-M409GT	M40x1,5	NW 29	19	60,0	40	49	30
1470106	BVND-M406GT	M40x1,5	NW 36	19	72,5	50	55	20
1470118	BVND-M506GT	M50x1,5	NW 36	19	72,0	50	59	20
1470107	BVND-M508GT	M50x1,5	NW 48	19	72,5	65	69	10
1470142	BVND-M638GT	M63x1,5	NW 48	19	72,0	65	75	10