



Straight conduit-connector IP66 PG

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1410640	BVND-P07MGT-11	PG7/12,5	NW 7	11	34,5	14	16.5	100
-	BVND-P070GT-8	PG7/12,5	NW 10	8	33,5	17	20	100
-	BVND-P070GT-11	PG7/12,5	NW 10	11	36,5	17	20	100
-	BVND-P09MGT-11	PG9/15,2	NW 7	11	34,5	14	20	100
1410641	BVND-P090GT-11	PG9/15,2	NW 10	11	36,5	17	20	100
-	BVND-P092GT-11	PG9/15,2	NW 12	11	39,0	20	23.5	100
-	BVND-P11MGT-11	PG11/18,6	NW 7	11	34,5	14	23	100
-	BVND-P110GT-8	PG11/18,6	NW 10	8	33,5	17	23	100
-	BVND-P110GT-11	PG11/18,6	NW 10	11	36,5	17	23	100
1410642	BVND-P112GT-11	PG11/18,6	NW 12	11	39,0	20	23.5	100
-	BVND-P117GT-11	PG11/18,6	NW 17	11	47,5	26	29.5	100
-	BVND-P13MGT-11	PG13,5/20,4	NW 7	11	34,5	14	26	100
-	BVND-P130GT-11	PG13,5/20,4	NW 10	11	36,5	17	26	100
-	BVND-P137GT-11	PG13,5/20,4	NW 17	11	47,5	26	29.5	100
-	BVND-P162GT-11	PG16/22,5	NW 12	11	39,0	20	27.5	100
1410643	BVND-P167GT-11	PG16/22,5	NW 17	11	47,5	26	29.5	100
-	BVND-P163GT-11	PG16/22,5	NW 23	11	51,0	32	37	50
1410644	BVND-P213GT	PG21/28,3	NW 23	12	52,0	32	37	50
1410645	BVND-P299GT	PG29/37,0	NW 29	12	53,0	40	44	30
1410646	BVND-P366GT	PG36/47,0	NW 36	13	66,0	50	55	20
1410647	BVND-P488GT	PG48/59,3	NW 48	13	66,5	65	69	10