



Flange straight IP65

- For cable protection systems in a wide range of applications.
- Specially formulated polyamide 6.
- Flange seal FGO4 made from EPDM.
- Flange seal FGO4/01 made from NBR.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- High conduit pull-out strength.
- Selectable flange seal included.
- Very good chemical properties.
- Free of halogen and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G).

Specification

MATERIAL	Polyamide PA6
SEALING RING	EPDM
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP65
TEMPERATURE RANGE	-40°C...+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0 (V2)
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONDUIT SIZE	A MM	B MM	C MM	D MM	H MM	E MM	M	PCS/PACK
1410388	BGG-56	NW 56	82,0	97,0	-	66,0	42,0	60	4 x M6	10
1410390	BGG-70	NW 70	97,0	114,0	100,0	80,0	48,0	60	6 x M6	10
1410392	BGG-95	NW 95	126,0	146,0	131,0	108,0	53,0	74	6 x M6	10
1410393	BGG-125	NW 125	-	194,0	177,0	153,5	79,0	88,5	6 x M6	5