



## System support - one-piece with safety lid

- For machine building and installation applications.
- High-grade, specially formulated polyamide 6.
- One-piece construction.
- Very high impact resistance.
- Optimal axial strain relief due to integrated rib.
- Suitable for overhead installations due to safety lid.
- High retention forces.
- Quick mounting due to single hole fixing.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles-fine (T) and coarse (G).

## Specification

<b>MATERIAL</b>	Polyamide PA6
<b>TEMPERATURE RANGE</b>	-40°C...+105°C
<b>COLOUR</b>	Black RAL 9005
<b>FLAME CLASS</b>	UL94 V2
<b>GLOW WIRE TEST</b>	960°C acc. to EN 60695-2-10
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	CONDUIT SIZE	A MM	B MM	C MM	H MM	E MM	M	PCS/PACK
1410320	BFH-07-0	NW 7	17,0	20,0	21,5	13,5	40.5	M4	100
1410321	BFH-10-0	NW 10	20,5	20,0	24,5	13,5	47.5	M5	100
1410322	BFH-12-0	NW 12	24,0	20,0	27,0	16,5	54.5	M5	100
1410323	BFH-17-0	NW 17	30,0	20,0	34,0	20,0	68	M6	100
1410324	BFH-23-0	NW 23	38,5	20,0	42,0	24,0	85	M6	100
1410325	BFH-29-0	NW 29	45,5	20,0	48,0	27,0	99	M6	100
1410326	BFH-36-0	NW 36	55,5	20,0	56,0	31,0	119	M6	50
1410327	BFH-48-0	NW 48	67,5	20,0	68,0	37,0	143	M6	50