



Conduit Adapter IP66

- For industry and machine building.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMA conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G).

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONDUIT SIZE	SUITABLE FOR CONDUIT CONNECTOR SIZE NW A	L MM	D Ø MM	D1 Ø MM	PCS/PACK
BAVD-12/10GT	10	12	46	20	15.5	50
BAVD-17/10GT	10	17	53	20	21	50
BAVD-17/12GT	12	17	54	23.5	21	50
BAVD-23/10GT	10	23	54	20	28.5	30
BAVD-23/12GT	12	23	53	23.5	28.5	30
BAVD-23/17GT	17	23	62	29.5	28.5	30
BAVD-29/10GT	10	29	56.5	20	34.5	30
BAVD-29/12GT	12	29	55	23.5	34.5	30
BAVD-29/17GT	17	29	61	29.5	34.5	30
BAVD-29/23GT	23	29	64	37	34	30
BAVD-36/29GT	29	36	81	44	43	20
BAVD-48/36GT	36	48	88.5	53.5	55	10