



## Conduit Connection Splices IP66

- For industry and machine building.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMA conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G).

### Specification

<b>MATERIAL</b>	Polyamide PA6
<b>INGRESS PROTECTION</b>	IP66 stat. / IP54 dyn.
<b>TEMPERATURE RANGE</b>	-40°C...+105°C
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	EN 60529 / DIN 40050 / IEC 60529
<b>FLAME CLASS</b>	UL94 V0 (V2)
<b>GLOW WIRE TEST</b>	960°C acc. to EN 60695-2-10
<b>HALOGEN-FREE</b>	Yes

## Variants

ARTICLE NO.	CONDUIT SIZE	H MM	E1 MM	PCS/PACK
BVSGD-1212GT	NW 12	66	23.5	50
BVSGD-1717GT	NW 17	89	30	50
BVSGD-2323GT	NW 23	103	37	20
BVSGD-2929GT	NW 29	100	44	20
BVSGD-3636GT	NW 36	130	53	10
BVSGD-4848GT	NW 48	136	61	10