



Metric adapter to solid metal tube

Adapter for connection of solid metal tubes with flexible conduits
 High-grade, specially formulated polyamide 6
 High conduit pull-out strength
 Very good chemical properties
 Fits both conduit profiles - fine (T) and coarse (G)
 Temperature: - 50 ... + 105 °C
 Free from halogens and cadmium
 Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6
TEMPERATURE RANGE	-50°C...+105°C
COLOUR	Black

Variants

ARTICLE NO.	DESCRIPTION	CONDUIT SIZE	L MM	A MM	DI1 MM	DI2 MM	PCS/PACK
BVNR-REM162	M16	12	54	26	16	23.5	50
BVNR-REM162-24	M16 with jubilee clip	12	54	26	16	23.5	50
BVNR-REM187	M18	17	65	26.5	18.5	30	50
BVNR-REM187-28	M18 with jubilee clip	17	65	26.5	18.5	30	50
BVNR-REM207	M20	17	65	28	20	30	50
BVNR-REM207-28	M20 with jubilee clip	17	65	28	20	30	50
BVNR-REM253	M25	23	71	30	26	37	30
BVNR-REM253-32	M25 with jubilee clip	23	71	30	26	37	30
BVNR-REM329	M32	29	71	30.5	32	44	20
BVNR-REM329-44	M32 with jubilee clip	29	71	30.5	32	44	20
BVNR-REM406	M40	36	90	36	40	53.5	20
BVNR-REM406-50	M40 with jubilee clip	36	90	36	40	53.5	20
BVNR-REM508	M50	48	90	35.5	50	66	10
BVNR-REM508-65	M50 with jubilee clip	48	90	35.5	50	66	10