



## PG adapter to solid metal tube

Adapter for connection of solid metal tubes with flexible conduits  
 High-grade, specially formulated polyamide 6  
 High conduit pull-out strength  
 Very good chemical properties  
 Fits both conduit profiles - fine (T) and coarse (G)  
 Temperature: - 50 ... + 105 °C  
 Free from halogens and cadmium  
 Fits both conduit profiles - fine (T) and coarse (G)

### Specification

<b>MATERIAL</b>	Polyamide 6
<b>TEMPERATURE RANGE</b>	-50°C...+105°C
<b>COLOUR</b>	Black

## Variants

ARTICLE NO.	DESCRIPTION	CONDUIT SIZE	L MM	A MM	D11 MM	D12 MM	PCS/PACK
BVNR-RE12	PG11	12	54	25	18.5	26	50
BVNR-RE12-24	PG11 with jubilee clip	12	54	25	18.5	26	50
BVNR-RE1317	PG13	17	65	28	20.4	30	50
BVNR-RE1317-28	PG13 with jubilee clip	17	65	28	20.4	30	50
BVNR-RE17	PG16	17	65	28	22.5	30	50
BVNR-RE17-28	PG16 with jubilee clip	17	65	28	22.5	30	50
BVNR-RE23	PG21	23	71	30	28.3	37	30
BVNR-RE23-32	PG21 with jubilee clip	23	71	30	28.3	37	30
BVNR-RE29	PG29	29	70.5	30	37	45	20
BVNR-RE29-44	PG29 with jubilee clip	29	70.5	30	37	45	20
BVNR-RE36	PG36	36	84.5	30	47	56	20
BVNR-RE36-50	PG36 with jubilee clip	36	84.5	30	47	56	20
BVNR-RE48	PG48	48	90	35	59.3	67.5	10
BVNR-RE48-65	PG48 with jubilee clip	48	90	35	59.3	67.5	10
BVNR-RE1917	3/4"	17	65	28	19	29.5	50
BVNR-RE2523	1"	23	71	30	25.5	37	30
BVNR-RE3129	1 1/4"	29	71	30	32	44	10
BVNR-RE3836	1 1/2"	36	130	76	38	53.5	10