



## DAF Inserts 68x34 for FL13 RAL 7035

- "Free placement" of openings
- Interchangeable inserts. Possible to change configuration later on.
- KLIKSEAL® or cable gland installation in the flange.
- "Pop-out" membranes.
- IP65 (Integrated sealing)

### Specification

<b>INFORMATION_KLIKSEAL</b>	(1) Unstressed material.
<b>MATERIAL</b>	Fiberglass re-inforced Polypropylene and TPE - UL listed material
<b>INGRESS PROTECTION</b>	IP65
<b>TEMPERATURE RANGE</b>	-20°C....+125°C (1)
<b>COLOUR</b>	Lightgrey RAL 7035
<b>TEST STANDARD</b>	EN IEC 60670-1:2021 + A11
<b>SEMKO REPORT</b>	2300073
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	FOR USE WITH FRAME	FOR CABLE Ø MM	PCS/PACK
2665414	13 6834 2X8-17 G	Insert 13 68x34, 2x 8-17mm	FL13	8-17	10
2665415	13 6834 2X6-13 G	Insert 13 68x34, 2x M20	FL13	6-13	10
2665416	13 6834 10X4-10 G	Insert 13 68x34, 10x 4-10mm	FL13	4-10	10