



## DAF Inserts 68x68 for FL21 RAL 9005

- "Free placement" of openings
- Interchangeable inserts. Possible to change configuration later on.
- KLIKSEAL® or cable gland installation in the flange.
- "Pop-out" membranes.
- IP65 (Integrated sealing)

### Specification

<b>INFORMATION_KLIKSEAL</b>	(1) Unstressed material.
<b>MATERIAL</b>	Fiberglass re-inforced Polypropylene and TPE - UL listed material
<b>INGRESS PROTECTION</b>	IP65
<b>TEMPERATURE RANGE</b>	-20°C....+125°C (1)
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	EN IEC 60670-1:2021 + A11
<b>SEMKO REPORT</b>	2300073
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	FOR USE WITH FRAME	FOR CABLE Ø MM	PCS/PACK
2665424	6868 2(8-17 5-10) B	Insert 21 68x68, 2x M25 + 2x M16	FL21	8-17, 5-10	10
2665425	6868 KO M50 M40 M32 B	Insert 21 68x68, Knockout M50, M40, M32	FL21	-	10
2665426	6868 9X7-14 B	Insert 21 68x68, 9x 7-14mm	FL21	7-14	10
2665427	6868 2(20-30 10-20) B	Insert 68x68 2x 10-20mm, 2x20-30mm	FL21	10-20, 20-30	10