



## DAF Prefabricated Flanges FL21 RAL 9005

- "Free placement" of openings
- Interchangeable inserts. Possible to change configuration later on.
- KLIKSEAL® or cable gland installation in the flange.
- "Pop-out" membranes.
- IP65 (Integrated sealing)

### Specification

<b>INFORMATION_KLIKSEAL</b>	(1) Unstressed material.
<b>MATERIAL</b>	Fiberglass re-inforced Polypropylene and TPE - UL listed material
<b>INGRESS PROTECTION</b>	IP65
<b>TEMPERATURE RANGE</b>	-20°C....+125°C (1)
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	EN IEC 60670-1:2021 + A11
<b>SEMKO REPORT</b>	2300073
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	SIZE	FOR CABLE Ø MM	L1 MM	H MM	L2 MM	PCS/PACK
2665419	2(8-17 5-10 6-13) 20X4-10 B	Flange FL21 20x 4-10mm, 2x M20, 2x M16, 2x M25	FL21	20x 4-10mm, 2x 6-13mm, 2x 5-10mm, 2x 8-17mm	214	9	90	10
2665420	2(8-17 6-13) 30X4-10 B	Flange FL21 30 x 4-10mm, 2 x M20, 2 x 8-17mm	FL21	30x 4-10mm, 2x 6-13mm, 2x 8-17mm	214	9	90	10
2665421	18X7-14 10X4-10 B	Flange FL21 18x 7-14mm + 10x 4-10mm	FL21	18x 7-14mm, 10x 4-10mm	214	9	90	10