



## DAF inserts 68x68 for FL21 RAL 7035

### Specification

<b>INFORMATION_KLIKSEAL</b>	(1) Unstressed material.
<b>MATERIAL</b>	Fiberglass re-inforced Polypropylene and TPE - UL listed material
<b>INGRESS PROTECTION</b>	IP65
<b>TEMPERATURE RANGE</b>	-20°C....+125°C (1)
<b>COLOUR</b>	Lightgrey RAL 7035
<b>TEST STANDARD</b>	EN IEC 60670-1:2021 + A11
<b>SEMKO REPORT</b>	2300073
<b>HALOGEN-FREE</b>	Yes

### Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	FOR USE WITH FRAME	FOR CABLE Ø MM	PCS/PACK
2665406	6868 2(8-17 5-10) G	Insert 21 68x68, 2x M25 + 2x M16	FL21	8-17, 5-10	10
2665407	6868 KO M50 M40 M32 G	Insert 21 68x68, Knockout M50, M40, M32	FL21	-	10
2665408	6868 9X7-14 G	Insert 21 68x68, 9x 7-14mm	FL21	7-14	10
2665409	6868 2(20-30 10-20) G	Insert 21 68x68, 2x 20-30mm + 2x 10-20mm	FL21	20-30, 10-20	10