



DAF Prefabricated Flanges FL21 RAL 7035

- "Free placement" of openings
- Interchangeable inserts. Possible to change configuration later on.
- KLIKSEAL® or cable gland installation in the flange.
- "Pop-out" membranes.
- IP65 (Integrated sealing)

Specification

INFORMATION_KLIKSEAL	(1) Unstressed material.
MATERIAL	Fiberglass re-inforced Polypropylene and TPE - UL listed material
INGRESS PROTECTION	IP65
TEMPERATURE RANGE	-20°C....+125°C (1)
COLOUR	Lightgrey RAL 7035
TEST STANDARD	EN IEC 60670-1:2021 + A11
SEMKO REPORT	2300073
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	SIZE	FOR CABLE Ø MM	L1 MM	H MM	L2 MM	PCS/PACK
2665401	2(8-17 5-10 6-13) 20X4-10 G	Flange FL21 20x 4-10mm, 2x M20, 2x M16, 2x M25	FL21	20x 4-10mm, 2x 6-13mm, 2x 5-10mm, 2x 8-17mm	214	9	90	10
2665402	2(8-17 6-13) 30X4-10 G	Flange FL21 30 x 4-10mm, 2 x M20, 2 x 8-17mm	FL21	30x 4-10mm, 2x 6-13mm, 2x 8-17mm	214	9	90	10
2665403	18X7-14 10X4-10 G	Flange FL21 18x 7-14mm + 10x 4-10mm	FL21	18x 7-14mm, 10x 4-10mm	214	9	90	10