



Slotted & Closed Inserts

Specification

MATERIAL	TPE-V
TEMPERATURE RANGE	-40°C...+135°C
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	PCS/PACK
1457298	UNI Split Gland M20	6,0 - 8,0	25
1457299	UNI Split Gland M20	7,0 - 9,5	25
1457300	UNI Split Gland M20	8,0 - 10,5	25
1457301	UNI Split Gland M20	9,5 - 13,0	25
1457302	UNI Split Gland M20	12 - 14,5	25
1457304	UNI Split Gland M20	Blind/Closed	25
UF554P9	UNI Split Gland M25 & UNI Flange	8,0 - 9,5	25
1477338	UNI Split Gland M25 & UNI Flange	9,0 - 11,0	25
1477339	UNI Split Gland M25 & UNI Flange	11,0 - 13,0	25
1477340	UNI Split Gland M25 & UNI Flange	12,0 - 15,0	25
1477341	UNI Split Gland M25 & UNI Flange	14,0 - 18,0	25
1477342	UNI Split Gland M25 & UNI Flange	18,0 - 20,0	25
1477433	UNI Split Gland M25 & UNI Flange	Blind/Closed	25
UF555P8	UNI Split Gland M32	6,0 - 8,0	25
1457317	UNI Split Gland M32	10,0 - 13,0	25
1457318	UNI Split Gland M32	12,5 - 15,5	25
1457319	UNI Split Gland M32	15,0 - 18,0	25
1457320	UNI Split Gland M32	18,0 - 20,5	25
1457321	UNI Split Gland M32	20,5 - 25,0	25
1457322	UNI Split Gland M32	25,0 - 26,5	25
1457323	UNI Split Gland M32	Blind/Closed	25