



Cable Connector IP68

- for quick and safely connecting two cables
- robust design for use in harsh environment conditions
- flexible to use and reusable multiple times
- solid and fine stranded conductor 0,2 - 4 mm², stranded conductor 0,2 - 2,5 mm²
- Rated voltage: 450 V, Rated current: 32 A

Specification

MATERIAL	Connecting Box: Polyamide PA6 GF30 V-0 Cover outer parts: Polyamide PA6 V-0 Cover inner parts: Polyamide PA6 V-2 and elastomers Inline splicing connector: Polycarbonate PC V-2 Mounting carrier: Polyamide PA
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-25°C...+85°C
TEST STANDARD	IEC 60670-1 IEC 60670-22 EN 60998-2-2

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	FOR CABLE Ø MM	L MM	L1 MM	H MM	H1 MM	L2 MM	SW1 MM	PCS/PACK
1459907	T320-9300-02	Cable Connector 3-pole	5 - 12	115	60	26,5	20	42	24	1
-	T320-9301-02	Cable Connector 3-pole with tiwrap clamps	5 - 12	157	102	26,5	20	42	24	1

