



## Jointing sleeve with cable gland IP68

- Two variants, screw-connection (1459904 & 1459903) and fast connection (1459905)
- Stationary laying of cables in cable ducts or suspended ceilings, stationary upper-plaster laying
- Quick and easy installation
- Suitable for narrow spaces
- 1459906 reduction sealing insert for 1459904

### Specification

<b>MATERIAL ENCLOSURE</b>	Polypropylene / (1459903) Polystyrene
<b>INGRESS PROTECTION</b>	IP68 - 5 bar (30 min)
<b>COLOUR</b>	Lightgrey RAL 7035
<b>FLAME PROTECTION</b>	Glow wire test 750°C acc. to DIN EN 60695-2-1/1 (terminalblock 960°C)
<b>HALOGEN-FREE</b>	Yes

### Variants

E-NUMBER	DESCRIPTION	FOR CABLE Ø MM	H MM	SW1 MM	SW2 MM	PCS/PACK
1459904	Terminal block 5x(1,5-2,5mm <sup>2</sup> )	9 - 17	134	27	29	15
1459903	Terminal block 5x(1,5-6mm <sup>2</sup> )	10 - 18	165	32	33	10
1459905	Splicing connector 3x(1,5-4mm <sup>2</sup> )	7 - 17	134	27	29	15
1459906	Reducing sealing insert for smaller cable Ø	7 - 12	-	0	0	25