



## Busbar, Fork

Type G-3T... forks in the middle of the rail packet. Other lengths on request.

### Specification

MATERIAL ISOLATION	PC / ABC-2 - ABS-3
MATERIAL	Copper E - Cu58 F25
RATED VOLTAGE	600 V
OPERATING RATED CURRENT IS/PHASE 10 MM <sup>2</sup>	63A
OPERATING RATED CURRENT IS/PHASE 16 MM <sup>2</sup>	80A

## Variants

ARTICLE NO.	NO. OF MODULES	NUMBER OF PHASES	LENGTH MM	PCS/PACK
G-1L-1000/10	57.00	1	1000	50
G-1L-210/10	12.00	1	210	100
G-2L-1000/10	57.00	2	1000	20
G-2L-210/10	12.00	2	210	50
G-2L-1000/16	57.00	2	1000	20
G-2L-210/16	12.00	2	210	50
G-3T-1000/10	57.00	3	1000	10
G-3T-210/10	12.00	3	210	50
G-3L-1000/10	57.00	3	1000	20
G-3L-210/10	12.00	3	210	50
G-3L-1000/16	57.00	3	1000	10
G-3L-210/16	12.00	3	210	50
G-3T-1000/16	57.00	3	1000	10
G-3L-228/10	13.00	3	228	50
G-3L-228/16	13.00	3	228	50