



Load Break Switch 3-pole 3 modules 40A

Specification

RATED THERMAL CURRENT I _{THE} (A)	63
BACK-UP FUSE (A)	63
RATED OPERATIONAL CURRENT AC21 IE (A)	400/415V = 63 A 500V = 63 A 690V = 63 A
RATED OPERATIONAL CURRENT AC22 IE (A)	400/415V = 40 A 500V = 40A 690V = 40 A
RATED OPERATIONAL CURRENT AC23 IE (A)	400/415V = 32 A 500V = 32 A 690V = 32 A
RATED OPERATIONAL POWER AC-23 (KW)	400/415V = 15 kW 500V = 22 kW 690V = 30 kW
RATED SHORT-CIRCUIT CAPACITY (KA)	50
MECHANICAL ENDURANCE (NUMBER OF OPERATIONS)	50.000
TERMINALS / BOLT SIZE (MM ²)	1,5 - 16
FASTENING TORQUE	1,8 Nm
MODULE WIDTH	3 modules (54mm)
STANDARDS	IEC 60 947-3, IEC 60 269-2, UL 508

Variants

E-NUMBER	ARTICLE NO.	NUMBER OF POLES	RATED OPERATIONAL CURRENT AC-22	RATED OPERATIONAL CURRENT AC-23	PCS/PACK
2154455	KUE340	3	40A	32A	1/20